

WHAT IS CLAIMED IS:

1. A dividing head using a multiple lead type worm, comprising:
  - a hollow worm body having multiple lead type worm teeth;
  - a drive shaft fitted into a hollow portion of said worm body; and
  - an assembler having an annular portion which is coaxial with said drive shaft, displaces radially to press said worm body and said drive shaft to couple both by frictional engagement.
2. The dividing head as claimed in claim 1, wherein said assembler includes a cylinder which forms said annular portion, the cylinder being disposed between said worm body and said drive shaft, having a fluid reservoir in an interior of the cylinder, and being expandable with the outer periphery and the inner periphery of said cylinder displaced outwardly and inwardly in the radial direction by the pressure of the reservoired fluid; a flange integrally following one end of said cylinder and having a screw hole connected to said reservoir; and a screw member screwable into said screw hole; and
  - wherein said worm body has a fitting hole for receiving said cylinder, the fitting hole having a larger diameter than that of said drive shaft in an axial position corresponding to said worm teeth.
3. The dividing head as claimed in claim 1, wherein said worm body has an elastically deformable sleeve at one end, wherein said assembler has a first

ring fitted on the outside of said sleeve, a second ring fitted on the outer periphery of said first ring on the worm teeth side, a third ring fitted on the outer periphery of said first ring on the opposite side to the worm teeth, and a plurality of screw members screwed into said second ring, penetrating said third ring, and wherein said first, second and third rings displace said sleeve in its axial direction according to the amount of screwing of said screw member into said second ring.

4. The dividing head as claimed in claim 3, wherein said first ring has an outer periphery having a section shaped like a mountain by two truncated conical faces, wherein said second ring has an inner periphery with a truncated conical shape corresponding to one of said truncated conical faces, the inner periphery of the second ring being fitted to one of said truncated conical faces, and wherein said third ring has an inner periphery with a truncated conical shape corresponding to the other of said truncated conical faces of said first ring, the inner periphery of the third ring being fitted to the other of said truncated conical faces.

5. The dividing head as claimed in claim 1, wherein said dividing head is a multishaft dividing head comprising plural sets of said worm bodies and said assemblers, and wherein at least two sets of said worm bodies are assembled into said drive shaft in common.